



**Minelab Electronics
Pty. Limited**

ABN 35 008 208 446
2 Second Avenue
Mawson Lakes SA 5095
Australia

PO BOX 35
Salisbury South SA 5106
Australia

Technical information – Charging

These consumer electrical products accept an input voltage not exceeding 264VAC, these products are not intended for use with lighting controllers.

Part Number	Description	Comment	Description of use
0302-0076 (3011-0203) / FRA-024-S24-I	Plug Pack, Mains Li-ion Battery	Input voltage: 100-240VAC Output voltage: 24VDC	This electrical device converts alternating current (AC) from a wall outlet into direct current (DC) to supply the connected device. This AC adapter is used for charging a Minelab GPX 5000 Metal Detector battery pack.
0302-0091 (3011-0339) / XY12S- 1201000Q-UZ	PLUG PACK MAINS UNI- HEAD 12V 1A 2.1MM	Input voltage: 100-240VAC Output voltage: 12VDC	The electrical device that converts alternating current (AC) from a wall outlet into direct current (DC) to supply the connected device. This AC adapter is used for charging a Minelab Gold Monster 1000 metal detector battery pack.
0302-0097 (3011-0407) / U411	Charger, 4xAA, USB	Input voltage: 5VDC Output voltage: 2.8VDC	This USB powered electrical device is used for charging AA Ni-MH batteries. This USB charger is used for charging batteries for the Minelab Vanquish series metal detector.
3011-0128 (78-16052) / FRA030E-S18-I	Kit, Acc. BC 10 Charger Station Only	Input voltage: 90-264VAC Output voltage: 18VDC	This electrical device converts alternating current (AC) from a wall outlet into direct current (DC) to supply the connected device. This AC adapter powers a battery charger used for charging Minelab GPZ 7000 Metal Detector batteries.
4523-0048 (3011-0368)	Cable Assy USB to Mag Connector	Input voltage: 5VDC Output voltage: 5VDC	This is a custom USB cable . It has a USB type-A connector on one end and a custom magnetic connector on the other. It is used for charging the batteries on a Minelab Equinox series Metal Detector.
78-0302-0001 (3011-0239)	Charger, Battery 110V - 12V	Input voltage: 110VAC Output voltage: 14.3VDC	The electrical device that converts alternating current (AC) from a wall outlet into direct current (DC) to supply the connected device.

We Change People's Fortunes

Tel: +61 (08) 8238 0888

www.minelab.com



**Minelab Electronics
Pty. Limited**

ABN 35 008 208 446
2 Second Avenue
Mawson Lakes SA 5095
Australia



PO BOX 35
Salisbury South SA 5106
Australia

			This AC adapter is used for charging a Minelab Excalibur II Metal Detector battery pack.
78-16052 (3011-0243) / FRA030E-S18-I	Plug Pack, Mains	Input voltage: 90-264VAC Output voltage: 18VDC	This electrical device converts alternating current (AC) from a wall outlet into direct current (DC) to supply the connected device. This AC adapter powers a battery charger used for charging Minelab CTX3030 Metal Detector batteries.

Sincerely,

			
Charles Edwards	Position: Compliance Officer, Engineering	Date: 26 February 2025	

Appendix 1

Part Number	Picture / Image
0302-0076	  General Description: GPX 5000 Metal Detector: https://www.minelab.com/metal-detectors/gpx-5000 Technical Specifications: GPX 5000 - Detectores User's Manual: Instruction Manual GPX 4800-5000 SPANISH (4901-0098-2).pdf Starting Guide: GPX 5000 Quick Start Guide EN ES PT PL.pdf Brochure: USA-GPX 4800 5000-Brochure-SPANISH-LoRes.pdf
0302-0091	 

	General Description: Gold Monster 1000 Metal Detector: https://www.minelab.com/metal-detectors/gold-monster-1000 Technical Specifications: GOLD MONSTER 1000 - Detectores Starting Guide: 4901-0244-4 GSG, Gold Monster 1000 ES, RU, ZH, MN WEB.pdf Brochure: 4907-0887-1 Brochure, GOLD MONSTER 1000 A4 2p GM LATAM ES WEB.pdf
0302-0097	 General Description: Vanquish series Metal Detector: https://www.minelab.com/metal-detectors/vanquish-540 Technical Specifications: VANQUISH 540 - Detectores User's Manual: 4901-0366-1 Inst. Manual, VANQUISH 440 540 ES WEB.pdf Starting Guide: VANQUISH 440 540 Getting Started Guide ES.pdf Brochure: 4907-1029-1 Vanquish Brochure Foldable SP WEB.pdf

3011-0128

- Universal Input, Wall mount style
- Interchangeable plug available (kit sold separately)
- Single output 30W, Anywhere output voltage 11 ~50VDC
- Meets CEC level V or IV

SPECIFICATIONS

Input Voltage Range.....90~264VAC
Input Current (rms).....0, 7A Max.
Efficiency.....80% type, at full load
(Avg. Eff.) Fit requirement for CEC Models
Output Voltage.....[anywhere output voltage].....11~50VDC
Voltage Regulation.....± 5% max.
Max. Power.....30W



Model Number	Output Voltage (VDC)	Output Current (A)	Output Max. Watts	CEC *
FRA030E-S12-x	11~13	2.73~2.3	30W	V
FRA030E-S15-x	13~16	2.3~1.87	30W	V
FRA030E-S18-x	16~21	1.87~1.43	30W	V
FRA030E-S24-x	21~27	1.43~1.11	30W	V
FRA030E-S30-x	27~33	1.11~0.91	30W	IV



General Description: GPZ 7000 Metal Detector: <https://www.minelab.com/metal-detectors/gpz-7000>

Technical Specifications: [GPZ 7000 - Detectores](#)


User's Manual: [4901-0178-3 Inst Manual GPZ 7000 ES WEB.pdf](#)

Starting Guide: [Field Guide GPZ 7000 GB Ferrite ES WEB.pdf](#)

Brochure: [4907-0943-1 Brochure, GPZ 7000 Software Upgrade No.2 ES WEB.pdf](#)

4523-0048

CONTACT: 4523-0048 FOR C-2000 AC C-2000 WORKING SYSTEM
<接触彈力: 70g±20g在1.0mm的工作行程>
Full stroke: 1.40mm
<最大行程: 1.40mm>
Life test: 50,000 cycles
<寿命: 50,000次>
Electrical: <电气性能>
Rated voltage & current: DC 12V, 2A Max.
<额定电压, 电流: DC 12V, 2A>
Contact resistance: 50 milliohm Max.
<接触电阻: 50 milliohm Max.>
When the current is more than 1A, then need to
add a delay circuit(3 seconds)
<当电流大于1A时, 则需要增加延时电路(3秒)>
100% open & short test.
<100%开, 短路测试>
The product must be checked for use by male and female.
<产品必须经公母对接使用检查>
RoHS TSCA compliant product
<符合RoHS, TSCA产品要求>





General Description: Equinox series Metal Detector: <https://www.minelab.com/metal-detectors/equinox-800>

Technical Specifications: [EQUINOX 800 - Detectores](#)

User's Guide: [4901-0273-1 Inst. Manual, EQUINOX 600 800 ES.pdf](#)

Starting Guide: [4901-0260-2 GSG, EQUINOX 600 800 ES WEB.pdf](#)

Brochure: [4907-0985-1 Brochure, EQUINOX Series A4 4p-ES_WEB.pdf](#)

78-0302-0001



General Description: Excalibur II Metal Detector: <https://www.minelab.com/metal-detectors/excalibur-ii>

Technical Specifications: [Excalibur II - Detectores](#)

